

带标准内圈的 Y 轴承

基本尺寸		基本额定载荷			疲劳载荷极限	极限转速	型号
d	D	B	C	C ₀	P _u		
mm		kN			kN	r/min	
17	40	12	9.56	4.75	0.2	12000	1726203-2RS1
20	47	14	12.7	6.55	0.28	10000	1726204-2RS1
25	52	15	14	7.8	0.335	8500	1726205-2RS1
25	62	17	22.5	11.6	0.49	7500	1726305-2RS1
30	72	19	28.1	16	0.67	6300	1726306-2RS1
30	62	16	19.5	11.2	0.475	7500	1726206-2RS1
35	72	17	25.5	15.3	0.655	6300	1726207-2RS1
35	80	21	33.2	19	0.815	6000	1726307-2RS1
40	80	18	30.7	19	0.8	5600	1726208-2RS1
40	90	23	41	24	1	5000	1726308-2RS1
45	100	25	52.7	31.5	1.34	4500	1726309-2RS1
45	85	19	33.2	21.6	0.915	5000	1726209-2RS1
45	85	19	33.2	21.6	0.915	5000	1726209 B-2RS1/VP274
45	100	25	52.7	31.5	1.34	4500	1726309 B-2RS1/VP274
50	110	27	61.8	38	1.6	4300	1726310-2RS1
50	90	20	35.1	23.2	0.98	4800	1726210-2RS1
50	110	27	61.8	38	1.6	4300	1726310 B-2RS1/VP274
55	100	21	43.6	29	1.25	4300	1726211-2RS1
60	110	22	52.7	36	1.53	4000	1726212-2RS1