

双向推力球轴承

基本尺寸				基本额定载荷		疲劳载荷极限	额定转速		订货号	
d	D	H	H ₁	C	C ₀	P _u	参考转速	极限转速	轴承	调心座垫圈
mm				kN		kN	r/min			
10	32	22		15.9	25	0.915	5300	7500	52202	
15	40	26		21.2	37.5	1.4	4300	6000	52204	
20	47	28		26.5	50	1.86	3800	5300	52205	
20	52	34		34.5	60	2.24	3200	4500	52305	
20	70	52		70.2	122	4.5	2200	3200	52406	
25	52	29		25.1	51	1.86	3600	5000	52206	
25	60	38		35.8	65.5	2.4	2800	4000	52306	
25	80	59		76.1	137	5.1	2000	2800	52407	
25	60	41.3	46	35.8	65.5	2.4	2800	3800	54306	U 306
30	62	34		35.1	73.5	2.7	3000	4300	52207	
30	68	36		44.2	96.5	3.6	2800	3800	52208	
30	68	44		49.4	96.5	3.55	2400	3400	52307	
30	78	49		61.8	122	4.5	2200	3000	52308	
30	90	65		95.6	183	6.8	1800	2400	52408	
30	62	37.8	42	35.1	73.5	2.7	2800	4000	54207	U 207
30	68	38.6	44	44.2	96.5	3.6	2800	3800	54208	U 208
30	78	54.1	59	61.8	122	4.5	2200	3000	54308	U 308
30	68	47.2	52	49.4	96.5	3.55	2400	3400	54307	U 307
35	73	37		39	86.5	3.2	2600	3600	52209	
35	85	52		76.1	153	5.6	2000	2800	52309	
35	100	72		124	240	9	1600	2200	52409	
35	100	78.9	86	124	240	9	1500	2000	54409	U 409
35	85	56.2	62	76.1	153	5.6	1900	2800	54309	U 309
35	73	39.6	45	39	86.5	3.2	2600	3600	54209	U 209
40	110	83.2	92	148	305	11.4	1400	1900	54410	U 410
40	95	64.7	70	81.9	170	6.3	1700	2400	54310	U 310
40	95	58		81.9	170	6.3	1800	2600	52310	
40	78	39		49.4	116	4.3	2400	3400	52210	
45	90	49.6	55	58.5	134	4.9	2200	3000	54211	U 211
45	120	87		195	400	14.6	1300	1800	52411	

45	105	64		101	224	8.3	1600	2200	52311	
45	90	45		58.5	134	4.9	2200	3000	52211	
50	110	70.7	78	101	224	8.3	1500	2200	54312	U 312
50	110	64		101	224	8.3	1600	2200	52312	
50	130	93		199	430	16	1200	1700	52412 M	
50	95	46		59.2	140	5.1	2000	2800	52212	
55	250	107		234	550	19.3	800	1100	52414 M	
55	115	64		106	240	8.8	1600	2200	52313	
55	125	72		135	320	11.8	1400	2000	52314	
55	100	47		60.5	150	5.5	2000	2800	52213	
55	105	47		62.4	160	5.85	1900	2600	52214	
60	135	79		163	390	14	1300	1800	52315	
60	110	47		63.7	170	6.2	1900	2600	52215	
65	140	86.1	95	159	390	13.7	1300	1800	54316	U 316
65	140	79		159	390	13.7	1300	1800	52316	
65	170	128.5	140	307	750	25	850	1200	54416 M	U 416
65	115	48		76.1	208	7.65	2400	3400	52216	
70	150	95.2	105	174	405	14	1100	1500	54317	U 317
70	125	55		97.5	275	9.8	1600	2200	52217	
75	135	62		112	290	116	1500	2000	52218	
